

APEX ATV TYRES





- UTILITY



AP06

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x12-9	4	AP06	9.5	645	290	5	35	194	430
25x12-9	6	AP06	9.5	645	290	7	48	223	495
22x7-10	4	AP06	5.5	545	180	14	97	170	377
22x10-10	4	AP06	8.0	559	256	14	97	173	385
22x11-10	4	AP06	9.0	559	268	5	35	149	330
22x11-10	6	AP06	9.0	559	268	7	48	173	385
24x11-10	4	AP06	9.0	620	270	5	35	173	385
24x11-10	6	AP06	9.0	620	270	7	48	198	440
25x12-10	4	AP06	9.5	645	245	5	35	194	430
25x12-10	6	AP06	9.5	645	245	7	48	223	495
23x8-11	4	AP06	6.5	584	195	5	35	115	255
23x8-11	6	AP06	6.5	584	195	7	48	131	290
24x8-11	4	AP06	6.5	610	195	5	35	124	275
24x8-11	6	AP06	6.5	610	195	7	48	144	320
24x9-11	4	AP06	7.0	610	207	5	35	140	310
24x9-11	6	AP06	7.0	610	207	7	48	164	365
24x10-11	4	AP06	8.0	620	240	5	35	153	340
24x10-11	6	AP06	8.0	620	240	7	48	178	395
24x8-12	4	AP06	6.5	610	190	5	35	119	265
24x8-12	6	AP06	6.5	610	190	7	48	140	310
25x8-12	4	AP06	6.5	623	194	5	35	131	290
25x8-12	6	AP06	6.5	623	194	7	48	153	340
25x8-12	8	AP06	6.5	623	194	10	69	209	465
25x10-12	4	AP06	8.0	645	235	5	35	164	365
25x10-12	6	AP06	8.0	645	235	7	48	189	420
25x10-12	8	AP06	8.0	645	235	10	69	216	480



AP06A

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
22x8-10	4	AP06A	6.5	554	196	5	35	108	240
22x8-10	6	AP06A	6.5	554	196	7	48	124	275
22x12.5-9	4	AP06A	9.5	559	274	5	35	133	295
22x12.5-9	6	AP06A	9.5	559	274	7	48	153	340



AP06B

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x8-12	6	AP06B	6.5	645	200	10	69	209	465
25x10-12	6	AP06B	8.0	623	230	10	69	216	480



- UTILITY



AP11

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
18x9.5-8	4	AP11	7.0	457	230	10	69	115	255
19x7-8	4	AP11	5.5	482	177	10	69	99	220
19x9.5-8	4	AP11	7.0	482	229	10	69	124	275
20x9.5-8	4	AP11	7.0	510	235	10	69	140	310
21x7-8	4	AP11	5.5	530	178	5	35	92	205
21x7-8	6	AP11	5.5	530	178	7	48	106	235



AP15

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
19x7-8	4	AP15	5.5	482	174	10	69	99	220



AP18

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x12-9	2	AP18	9.5	635	295	5	35	194	430
25x12-9	4	AP18	9.5	635	295	5	35	194	430



AP19

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
145/70-6	2	AP19	5.0	355	140	5	35	74	165
16x8-7	4	AP19	6.5	406	185	7	48	79	175



AP21

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
21x7-10	2	AP21	5.5	535	170	5	35	92	205
21x7-10	4	AP21	5.5	535	170	5	35	92	205
21x7-10	6	AP21	5.5	535	170	7	48	106	235
23.5x8-11	2	AP21	6.5	602	195	5	35	115	255



- UTILITY



SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
16x8-7	2	AP22	6.5	406	185	4	28	58	128
16x8-7	2	AP22	6.5	406	185	10	69	50	110
16x8-7	4	AP22	6.5	406	185	5	35	71	157
18x9.5-8	2	AP22	7.0	460	212	5	35	101	225
18x9.5-8	4	AP22	7.0	460	212	5	35	101	225
18x9.5-8	6	AP22	7.0	475	223	24	166	468	1040
20x7-8	2	AP22	5.5	494	177	5	35	88	195
20x7-8	2	AP22	5.5	494	177	10	69	113	250
20x7-8	4	AP22	5.5	494	177	5	35	88	195
22x11-8	2	AP22	9.0	558	277	5	35	153	340
22x11-8	4	AP22	9.0	558	277	5	35	153	340
22x11-9	2	AP22	9.0	565	271	5	35	153	340
22x11-9	4	AP22	9.0	565	271	5	35	153	340
22x11-10	2	AP22	9.0	558	270	5	35	149	330
22x11-10	4	AP22	9.0	558	270	5	35	149	330



SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
22x11-8	2	AP23	9.0	538	270	5	35	153	340
22x11-8	4	AP23	9.0	538	270	5	35	153	340
22x11-8	6	AP23	9.0	551	267	14	97	304	675



SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
22x11-8	4	AP24	9.0	567	275	5	35	153	340
22x11-8	4	AP24	9.0	567	275	7	48	178	395



SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
21x12-8	2	AP25	9.5	534	285	5	35	160	355



- UTILITY



AP29

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
16x8-7	4	AP29	6.5	406	185	7	48	79	175



AP30

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
145/70-6	2	AP30	5.0	355	145	5	35	74	165
19x7-8	4	AP30	5.5	480	166	10	69	99	220



AP33

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
145/70-6	2	AP33	5.0	355	145	5	35	74	165
145/70-6	4	AP33	5.0	355	145	5	35	74	165



AP39

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
22x11-10	4	AP39	9.0	521	266	5	35	149	330
22x11-10	6	AP39	9.0	521	266	7	48	173	385



AP40

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
18x8-8	4	AP40	6.5	455	210	10	69	79	175
19x7-8	4	AP40	5.5	468	173	10	69	99	220



- UTILITY



AP41

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
22x10-9	4	AP41	8.0	559	254	5	35	140	310
22x10-9	6	AP41	8.0	559	254	7	48	164	365
24x11-10	4	AP41	9.0	615	275	5	35	173	385
24x11-10	6	AP41	9.0	615	275	7	48	198	440
25x12-10	4	AP41	9.5	638	290	5	35	194	430
25x12-10	6	AP41	9.5	638	290	7	48	223	495
22x7-11	4	AP41	5.5	559	177	5	35	97	215
22x7-11	6	AP41	5.5	559	177	7	48	110	245
23x8-11	4	AP41	6.5	583	200	5	35	115	255
23x8-11	6	AP41	6.5	583	200	7	48	131	290
24x8-11	4	AP41	6.5	606	205	5	35	124	275
24x8-11	6	AP41	6.5	606	205	7	48	144	320
24x9-11	4	AP41	7.0	606	212	5	35	140	310
24x9-11	6	AP41	7.0	606	212	7	48	164	365
24x10-11	4	AP41	8.0	603	250	5	35	153	340
24x10-11	6	AP41	8.0	606	250	7	48	178	395
24x8-12	4	AP41	6.5	606	198	5	35	119	265
24x8-12	6	AP41	6.5	606	198	7	48	140	310
25x8-12	4	AP41	6.5	638	200	5	35	131	290
25x8-12	6	AP41	6.5	638	200	7	48	153	340
25x10-12	4	AP41	8.0	638	238	5	35	164	365
25x10-12	6	AP41	8.0	638	238	7	48	189	420



AP42

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
20x10-9	4	AP42	8.0	497	246	5	35	117	260
20x10-9	6	AP42	8.0	497	246	7	48	135	300



AP42B

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
20x10-9	4	AP42B	8.0	497	246	5	35	117	260
20x10-9	6	AP42B	8.0	497	246	7	48	135	300



- UTILITY



SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
145/70-6	4	AP61	4.5	355	133	5	35	74	165
16x8-7	4	AP61	6.5	401	186	7	48	79	175
16x6-8	4	AP61	4.5	390	156	5	35	51	114
18x9.5-8	4	AP61	7.0	455	218	10	69	115	255
19x7-8	4	AP61	5.5	483	180	5	35	99	220
19x9.5-8	4	AP61	7.0	481	236	5	35	124	275
20x10-10	4	AP61	8.0	509	252	5	35	117	260
21x7-10	4	AP61	5.5	530	177	5	35	92	205
22x7-10	4	AP61	5.5	559	177	5	35	99	220
22x7-10	6	AP61	5.5	559	177	7	48	115	255
22x10-10	4	AP61	8.0	556	253	5	35	135	300



SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
22x9-10	2	AP67	7.0	559	220	5	35	119	265
22x11-10	2	AP67	9.0	559	270	5	35	149	330



SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x11-10	6	AP75	9.0	640	272	7	48	205	455
25x9-11	6	AP75	7.0	635	222	7	48	173	385
25x10-11	6	AP75	8.0	645	243	7	48	189	420
25x8-12	6	AP75	6.5	632	203	7	48	153	340
25x10-12	6	AP75	8.0	632	249	7	48	189	420
26x9-12	6	AP75	7.0	662	219	7	48	185	410
26x12-12	6	AP75	9.5	666	290	7	48	234	520
27x9-12	6	AP75	7.0	688	225	7	48	198	440
27x12-12	6	AP75	9.5	700	288	7	48	248	550



- UTILITY



AP76

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x12-9	6	AP76	7.0	636	269	7	48	223	495
25x11-10	6	AP76	7.0	642	266	7	48	205	455
25x8-11	6	AP76	6.5	632	204	7	48	160	355
25x10-11	6	AP76	8.0	632	249	7	48	189	420
25x8-12	6	AP76	6.5	635	202	7	48	153	340
25x10-12	6	AP76	8.0	642	247	7	48	189	420
26x9-12	6	AP76	7.0	672	216	7	48	185	410
26x10-12	6	AP76	7.0	672	230	7	48	198	440
26x12-12	6	AP76	7.0	672	274	7	48	234	520
27x9-12	6	AP76	7.0	695	218	7	48	198	440
27x10-12	6	AP76	7.0	695	234	7	48	209	465
27x12-12	6	AP76	7.0	695	270	7	48	248	550
28x10-12	6	AP76	7.0	726	245	7	48	223	495
27x9-14	6	AP76	7.0	695	216	7	48	185	410
27x11-14	6	AP76	7.0	695	259	7	48	216	480

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
22x9.5-10	4	AP77	7.0	578	238	20	138	556	1235
24x12-10	4	AP77	7.8	639	280	20	138	770	1710
25x8-12	4	AP77	6.5	638	200	5	35	131	290
25x8-12	6	AP77	6.5	638	200	7	48	153	340
25x10-12	4	AP77	8.0	630	253	5	35	164	365
25x10-12	6	AP77	8.0	630	253	7	48	189	420



AP77



AP018

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
21x7-10	4	AP018	5.5	539	177	5	35	92	205
22x10-10	4	AP018	8.0	559	251	5	35	135	300



- UTILITY

- SIDE BY SIDE



AP50

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x8-12	4	AP50	6.5	630	202	5	35	131	290
25x8-12	6	AP50	6.5	630	202	7	48	153	340
25x8-12	8	AP50	6.5	643	203	24	166	495	1100
25x8R12	6	AP50	6.5	638	195	14	97	216	480
25x10-12	4	AP50	8.0	630	245	5	35	164	365
25x10-12	6	AP50	8.0	630	245	7	48	189	420
25x10-12	8	AP50	8.0	643	243	22	152	495	1100
25x10R12	6	AP50	8.0	638	234	14	97	266	590
26x9-12	6	AP50	7.0	662	228	7	48	185	410
26x9R12	6	AP50	7.0	664	220	14	97	257	570
26x10-12	6	AP50	8.0	662	250	7	48	198	440
26x11-12	6	AP50	9.0	662	286	7	48	216	480
26x11R12	6	AP50	9.0	664	283	14	97	306	680
26x12-12	6	AP50	9.5	662	296	7	48	234	520
27x9-12	6	AP50	7.0	686	228	7	48	198	440
27x10-12	6	AP50	8.0	686	255	7	48	209	465
27x12-12	6	AP50	9.5	686	296	7	48	248	550
26x8-14	6	AP50	6.5	662	202	7	48	160	355
26x10-14	6	AP50	8.0	662	245	7	48	194	430
27x9-14	6	AP50	7.0	686	222	7	48	185	410
27x9R14	6	AP50	7.0	685	220	14	97	263	585
27x10-14	6	AP50	8.0	686	245	12	83	338	750
27x11-14	6	AP50	9.0	686	275	7	48	216	480
27x11R14	6	AP50	9.0	685	275	14	97	320	710
27x12-14	6	AP50	9.5	686	296	12	83	338	750

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x8-12	4	AP51	6.5	635	203	5	35	131	290
25x8-12	6	AP51	6.5	635	203	7	48	153	340
25x10-12	4	AP51	8.0	635	248	5	35	164	365
25x10-12	6	AP51	8.0	635	248	7	48	189	420



AP51



AP62

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
26x9-12	6	AP62	7.0	655	220	7	48	185	410
26x11-12	6	AP62	9.0	655	274	7	48	216	480
26x9-14	4	AP62	7.0	660	230	5	35	153	340
26x11-14	4	AP62	9.0	660	280	5	35	178	395



- UTILITY

- SIDE BY SIDE



AP62A

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
26x9-14	6	AP62A	7.0	660	227	32	221	405	900
26x11-14	6	AP62A	9.0	660	281	34	235	504	1120

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
24x8-12	6	AP73	6.0	610	182	7	48	113	252
24x10-12	6	AP73	8.0	610	229	7	48	145	323
25x8-12	6	AP73	6.0	638	191	7	48	153	340
25x10-12	6	AP73	8.5	639	257	24	166	360	800
25x10-12	6	AP73	8.5	635	245	7	48	189	420
25x10R12	6	AP73	8.5	635	245	24	166	360	800
26x8-14	6	AP73	6.5	650	195	7	48	160	355
26x8R14	6	AP73	6.5	650	192	7	48	160	355
26x10-14	6	AP73	8.0	653	243	7	48	194	430
26x10R14	6	AP73	8.0	650	242	7	48	194	430



AP73



AP73A

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x11-12	6	AP73A	8.0	643	277	24	166	450	1000
25x11R12	6	AP73A	8.0	633	272	14	97	205	455

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x10-12	6	AP73B	8.0	642	228	7	48	189	420



AP73B



AP90

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x8-12	6	AP90	6.5	635	198	7	48	153	340
25x10-12	6	AP90	8.0	635	250	7	48	189	420
26x9-12	6	AP90	7.0	655	216	7	48	185	410
26x10-12	6	AP90	8.0	655	247	7	48	198	440
26x11-12	6	AP90	9.0	672	288	7	48	216	480
26x12-12	6	AP90	9.5	660	292	7	48	234	520



- UTILITY

- SIDE BY SIDE



AP92

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x8R12	6	AP92	6.5	635	195	7	48	153	340
25x10R12	6	AP92	8.0	635	251	7	48	189	420
26x8-14	6	AP92	6.5	655	195	7	48	160	355
26x10-14	6	AP92	8.0	655	240	7	48	194	430

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
24x8-12	4	AP006	6.0	610	183	12	83	135	300
24x9-12	4	AP006	6.0	610	203	18	124	293	650
25x8-12	6	AP006	6.5	633	199	7	48	153	340
25x10-12	6	AP006	8.0	633	246	7	48	189	420
26x9-12	6	AP006	7.0	652	224	7	48	185	410
26x11-12	6	AP006	9.0	652	276	7	48	216	480
27x9-12	6	AP006	7.0	689	228	18	124	320	710
27x11-12	6	AP006	9.0	690	280	18	124	376	835
26x9-14	6	AP006	7.0	652	223	7	48	178	395
26x11-14	6	AP006	9.0	652	275	7	48	209	465
27x9-14	6	AP006	7.0	692	221	18	124	306	680
27x11-14	6	AP006	9.0	685	280	18	124	369	820



AP006



AP011

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
24x8-12	6	AP011	6.5	610	204	7	48	140	310
25x8-12	6	AP011	6.5	639	201	7	48	153	340
25x10-12	6	AP011	7.0	635	250	7	48	189	420
26x9-12	6	AP011	7.0	660	227	7	48	185	410
26x10-12	6	AP011	7.0	655	233	7	48	198	440
26x12-12	6	AP011	8.0	655	285	7	48	234	520
27x9-12	6	AP011	7.0	686	227	7	48	198	440
27x12-12	6	AP011	8.0	686	281	7	48	248	550

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
26x9R14	8	AP016	8.0	666	234	20	138	333	740
26x11R14	8	AP016	8.0	671	258	24	166	518	1150



AP016



- UTILITY

- SIDE BY SIDE



SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
26x9R12	6	AP020	7.0	662	227	15	104	288	640
26x11R12	6	AP020	8.0	662	272	15	104	342	760
27x9R12	6	AP020	7.0	686	222	15	104	306	680
27x11R12	6	AP020	8.0	686	277	15	104	378	840
26x9R14	8	AP020	7.0	665	222	20	138	302	670
26x11R14	8	AP020	8.0	665	270	22	152	396	880
27x9R14	8	AP020	7.0	690	227	20	138	329	730
27x11R14	8	AP020	8.0	690	270	22	152	419	930
28x10R14	8	AP020	8.0	711	254	22	152	405	900

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
26x9R14	8	AP021	7.0	660	227	20	138	302	670
26x11R14	8	AP021	8.0	660	270	22	152	396	880
27x9R14	8	AP021	7.0	686	223	20	138	329	730
27x11R14	8	AP021	8.0	686	272	22	152	419	930
28x10R14	8	AP021	8.0	711	256	22	152	405	900
30x10R14	8	AP021	8.0	762	254	22	152	450	1000
28x10R15	8	AP021	8.0	711	250	22	152	405	900
30x10R15	8	AP021	8.0	762	262	22	152	450	1000



SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x8R12	8	AP027	6.5	640	196	18	124	250	555
25x10R12	8	AP027	8.0	640	252	18	124	306	680
26x9R12	8	AP027	7.0	660	224	20	138	320	710
26x11R12	8	AP027	8.0	660	275	20	138	401	890
27x9R12	8	AP027	7.0	688	220	20	138	338	750
27x11R12	8	AP027	8.0	688	271	22	152	428	950
26x9R14	8	AP027	7.0	660	227	20	138	302	670
26x11R14	8	AP027	8.0	660	268	22	152	396	880
27x9R14	8	AP027	7.0	686	220	20	138	329	730
27x11R14	8	AP027	8.0	686	268	22	152	419	930
30x10R14	8	AP027	8.0	760	254	22	152	450	1000



- UTILITY

- SIDE BY SIDE



AP029

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
26x9R12	8	AP029	7.0	664	225	18	124	322	715
26x12R12	8	AP029	8.0	665	274	18	124	387	860
27x9R12	8	AP029	7.0	688	222	18	124	342	760
27x11R12	8	AP029	8.0	688	268	18	124	407	905
27x9R14	8	AP029	7.0	688	221	18	124	331	735
27x11R14	8	AP029	8.0	688	265	18	124	396	880
30x10R14	8	AP029	8.0	762	254	22	152	450	1000



AP032

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
30x10-14	6	AP032	8.0	765	250	7	48	245	545
32x10-14	6	AP032	8.0	813	245	15	104	495	1100
32x10-15	6	AP032	8.0	813	245	15	104	450	1000
34x10-15	6	AP032	8.0	864	245	15	104	540	1200



AP035

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x8R12	6	AP035	6.5	635	204	18	124	250	555
25x10R12	6	AP035	8.0	635	242	18	124	306	680
26x9R14	6	AP035	7.0	666	220	18	124	288	640
26x11R14	6	AP035	9.0	666	275	18	124	349	775



AP036

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
27x9R14	8	AP036	7.0	686	227	20	138	329	730
27x11R14	8	AP036	9.0	686	275	22	152	419	930
28x10R14	8	AP036	8.0	711	248	22	152	405	900
29x9R14	8	AP036	7.0	736	227	20	138	374	830
29x11R14	8	AP036	9.0	736	275	22	152	450	1000
30x10R14	8	AP036	8.0	762	248	22	152	450	1000
28x10R15	8	AP036	8.0	711	245	22	152	405	900
30x10R15	8	AP036	8.0	762	245	22	152	450	1000



AP039

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
22x10-10	4	AP039	8.0	532	247	5	35	173	385
23x7-10	4	AP039	5.5	568	182	5	35	108	240

- UTILITY

- SIDE BY SIDE



AP048

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
28x10-14	6	AP048	8.0	711	242	18	124	450	1000
29x9-14	6	AP048	6.0	736	217	18	124	304	675
30x10-14	6	AP048	8.0	762	245	15	104	450	1000
30x10R14	8	AP048	8.0	767	249	15	104	450	1000
32x10-14	6	AP048	8.0	813	245	15	104	495	1100



AP051

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
28x10-14	6	AP051	8.0	711	235	10	69	313	695
30x11-14	6	AP051	8.0	766	267	10	69	385	855



AP052

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
28x13-14	6	AP052	10.0	711	310	10	69	351	780
30x14-14	6	AP052	10.0	768	330	10	69	473	1050



AP055

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x8-12	6	AP055	6.0	638	191	10	69	223	495
26x8-12	6	AP055	6.5	663	198	10	69	245	545
27x9-14	6	AP055	7.0	688	224	18	124	383	850



AP056

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x10-12	6	AP056	8.0	638	245	10	69	268	595
26x10-12	6	AP056	8.0	663	245	10	69	288	640
27x11-14	6	AP056	9.0	688	278	18	124	464	1030



- UTILITY

- SIDE BY SIDE



AP057

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
28x10R14	8	AP057	8.0	714	252	22	152	241	535
30x10R14	8	AP057	8.0	764	256	22	152	270	600
28x10R15	8	AP057	8.0	710	252	22	152	234	520
30x10R15	8	AP057	8.0	762	252	22	152	275	610
32x10R15	8	AP057	8.0	815	257	22	152	297	660



AP058

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x8-12	6	AP058	6.0	638	195	18	124	313	695
26x8-12	6	AP058	6.0	660	195	18	124	342	760
27x9R14	6	AP058	6.5	678	206	18	124	383	850
29x9R14	6	AP058	6.5	740	215	18	124	441	980



AP059

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
25x10-12	6	AP059	7.5	638	245	18	124	383	850
26x10-12	6	AP059	7.5	660	240	18	124	407	905
27x11R14	6	AP059	8.0	678	270	18	124	464	1030
29x11R14	6	AP059	8.0	740	270	18	124	515	1145



AP061

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
26x9R12	8	AP061	7.0	660	215	18	124	374	830
26x11R12	8	AP061	8.0	660	279	18	124	446	990
27x9R14	8	AP061	7.0	686	215	18	124	383	850
27x11R14	8	AP061	8.0	686	279	18	124	464	1030
28x10R14	8	AP061	8.0	711	250	18	124	448	995
30x10R14	8	AP061	8.0	762	250	18	124	509	1130



APOT99

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
27x10-12	6	APOT99	8.0	690	242	7	48	209	465
27x12-12	6	APOT99	9.5	690	285	7	48	248	550



- UTILITY

- SIDE BY SIDE



APW16

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
28x9.5R14	8	APW61	7.0	711	241	15	104	457	1016
30x9.5R14	8	APW61	7.0	762	241	15	104	457	1016
30x9.5R15	8	APW61	7.0	762	241	15	104	457	1016
30x9.5R16	8	APW61	7.0	762	241	15	104	457	1016

- SPORT

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
19x7-8	4	AP27	5.5	482	175	10	69	99	220



AP27



AP36

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
20x11-8	4	AP36	9.0	508	283	5	35	131	290
20x11-8	6	AP36	9.0	508	283	7	48	153	340
20x10-9	4	AP36	8.0	508	248	5	35	117	260
20x10-9	6	AP36	8.0	508	248	7	48	135	300
20x11-9	4	AP36	9.0	508	279	5	35	131	290
20x11-9	6	AP36	9.0	508	279	7	48	153	340
22x10-10	4	AP36	8.0	555	253	5	35	135	300

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
18x9.5-8	4	AP43	7.0	460	225	10	69	115	255
19x7-8	4	AP43	5.5	476	178	10	69	99	220



AP43



- SPORT



AP47

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
20x10-9	4	AP47	8.0	511	243	5	35	117	260
20x10-9	6	AP47	8.0	511	243	7	48	135	300
21x7-10	4	AP47	5.5	538	175	5	35	92	205
21x7-10	6	AP47	5.5	538	175	7	48	106	235



AP48

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
21x7-10	4	AP48	5.5	530	171	5	35	92	205
21x7-10	6	AP48	5.5	530	171	7	48	106	235
23x7-10	4	AP48	5.5	577	175	5	35	108	240
23x7-10	6	AP48	5.5	577	175	7	48	124	275



AP56

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
21x7-10	4	AP56	5.5	535	178	5	35	92	205
21x7-10	6	AP56	5.5	535	178	7	48	106	235
22x7-10	4	AP56	5.5	553	178	5	35	99	220
22x7-10	6	AP56	5.5	553	178	7	48	115	255
22x7-10	6	AP56	5.5	553	178	10	69	128	285

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
20x11-8	4	AP57	9.0	505	283	5	35	131	290
20x11-8	6	AP57	9.0	505	283	7	48	153	340
19x10-9	4	AP57	8.0	485	252	5	35	106	235
19x10-9	6	AP57	8.0	485	252	7	48	126	280
20x10-9	4	AP57	8.0	505	252	5	35	117	260
20x10-9	6	AP57	8.0	505	252	7	48	135	300
20x11-9	4	AP57	9.0	511	277	5	35	131	290
20x11-9	6	AP57	9.0	511	277	7	48	153	340
22x11-9	4	AP57	9.0	555	283	5	35	153	340
22x11-9	6	AP57	9.0	555	283	7	48	178	395
20x11-10	4	AP57	9.0	505	268	5	35	126	280
20x11-10	6	AP57	9.0	505	268	7	48	149	330
22x10-10	4	AP57	8.0	555	258	5	35	135	300
22x10-10	6	AP57	8.0	555	258	7	48	160	355



AP57



- SPORT



AP16

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
18x9.5-8	4	AP61	7.0	457	230	10	69	115	255
19x9.5-8	4	AP61	7.0	485	238	5	35	124	275



AP003

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
21x7-10	4	AP003	5.5	525	165	5	35	92	205



AP030

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
20x10-8	4	AP030	6.2	508	232	20	138	479	1065
20x10-8	4	AP030	7.0	508	240	20	138	479	1065
22.5x10-8	4	AP030	7.0	573	242	20	138	590	1310
25x12-9	4	AP030	10.0	645	312	20	138	824	1830



AP031

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
18x9.5-8	4	AP031	7.0	457	222	7	48	115	255
18x9.5-8	6	AP031	7.0	457	222	7	48	115	255

- MUD



AP08

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
22x11-8	4	AP08	9.0	538	260	5	35	153	340
22x11-8	6	AP08	9.0	538	260	7	48	178	395
22x12-8	4	AP08	9.5	600	275	7	48	194	430
25x13-9	4	AP08	10.5	642	315	7	48	241	535



AP34

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
22x11-8	4	AP34	9.0	565	255	20	138	450	1000
22x11-10	4	AP34	8.5	585	257	20	138	450	1000
23x10.5-12	4	AP34	8.5	579	265	20	138	450	1000



- SPORT

- SAND



AP63

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
22x10-9	4	AP63	8.0	559	250	5	35	135	300

- ON ROAD



AP49

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
22x10-10	4	AP49	8.0	562	260	30	207	135	300
22x10-10	6	AP49	8.0	562	260	32	221	277	615
23x7-10	4	AP49	5.5	580	182	30	207	108	240
26x8-14	4	AP49	6.5	660	210	25	172	338	750
26x8-14	6	AP49	6.5	660	210	25	172	338	750
26x10-14	4	AP49	8.0	665	260	25	172	416	925
26x10-14	6	AP49	8.0	665	260	25	172	416	925

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
20x10-9	4	AP54	8.0	505	257	10	69	117	260
21x7-10	4	AP54	5.5	535	181	10	69	92	205
25x8-12	4	AP54	6.5	635	213	25	172	131	290
25x8-12	4	AP54	6.5	635	213	25	172	331	735
25x8-12	6	AP54	6.5	635	213	30	207	153	340
25x10-12	4	AP54	8.0	635	248	25	172	162	360
25x10-12	4	AP54	8.0	635	248	25	172	331	735
25x10-12	6	AP54	8.0	635	248	30	207	187	415



AP54



AP83

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
20x6-14	4	AP83	6.0	506	158	10	69	189	420
22x7-15	4	AP83	6.0	567	171	10	69	194	430



AX27

SIZE	P.R.	PATTERN	RIM WIDTH (inch)	O.D (mm)	S.W (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
20x8-12	4	AX27	6.5	510	203	10	69	149	330
20x10-12	4	AX27	8.0	510	247	10	69	164	365



APEXWAY PRODUCTS CORP.

Taiwan Head Office:

14F-5, No.238, Shizheng N. 2nd Rd.,

Taichung, Taiwan, R.O.C

Tel:+886-4-2251-2251

Fax:+886-4-2251-2129

E-mail:apex@apexway.com.tw

sporttire.apexway.com.tw