



## - High Flotation Tire

Size	P.R.	TRA	Rim	TT/TL	S.W.	O.D.	Max Load	Pressure Inflate	Pattern
					(mm)	(mm)		(kPa)	
400/60-15.5	14	I3	13.00	TL	404	868	2500	360	C1C0022
400/60-15.5	16	I3	13.00	TL	404	868	2900	400	C1C0022
500/50-17	14	I3	13.00	TL	500	933	2246	360	C1C0022
500/50-17	16	I3	13.00	TL	500	933	3075	440	C1C0022



Size	P.R.	TRA	Rim	TT/TL	S.W.	O.D.	Max Load	Pressure Inflate	Pattern
					(mm)	(mm)		(kPa)	
500/60-22.5	12	I3	16.00	TL	500	1170	4125	240	C1C0013
500/60-22.5	16	I3	16.00	TL	503	1191	4375	300	C1C0013
500/60-22.5	18	I3	16.00	TL	503	1191	4875	320	C1C0013
550/60-22.5	12	I3	16.00	TL	550	1230	4500	210	C1C0013
550/60-22.5	16	I3	16.00	TL	537	1252	4875	280	C1C0013
600/50-22.5	16	I3	20.00	TL	592	1172	5150	260	C1C0013
600/55-22.5	16	I3	20.00	TL	592	1229	5000	200	C1C0013
650/50-22.5	16	I3	20.00	TL	645	1224	4500	200	C1C0013
700/40-22.5	16	I3	24.00	TL	699	1145	4500	170	C1C0013
700/50-22.5	16	I3	24.00	TL	699	1270	5600	180	C1C0013
710/40-22.5	16	I3	24.00	TL	711	1153	4500	170	C1C0013

Size	P.R.	TRA	Rim	TT/TL	S.W.	O.D.	Max Load	Pressure Inflate	Pattern
					(mm)	(mm)		(kPa)	
360/60-22.5	12	I3	11.75	TL	364	1003	1750	160	C1C0024
385/65-22.5	18	I3	11.75	TL	388	1071	4500	770	C1C0024
400/55-22.5	16	I3	13.00	TL	403	1011	3075	320	C1C0024
500/45-22.5	16	I3	16.00	TL	503	1021	3350	280	C1C0024
500/60-22.5	16	I3	16.00	TL	503	1191	4375	300	C1C0024
500/60-22.5	18	I3	16.00	TL	503	1191	4875	320	C1C0024
550/45-22.5	16	I3	16.00	TL	537	1066	4375	280	C1C0024
600/50-22.5	16	I3	20.00	TL	591	1172	5150	260	C1C0024

