

APEX[®]

APEX MOTORCYCLE & SCOOTER TYRES



Standard Street Sport





A1082



A1689

SIZE	PATTERN	LOAD/SPEED	TT / TL	RIM WIDTH (in.)	O.D. (inch/mm)	S.W. (inch/mm)	MAX LOAD (lbs/kgs)	INFLATE (psi/kgf/cm2)	E-MARK
70/90-17	A1082	38P	TL	1.60	22.0/558	2.7/69	342/155	33/2.3	-
80/90-17	A1082	44P	TL	1.85	22.7/576	3.1/80	419/190	33/2.3	✓
90/80-17	A1082	46P	TL	2.15	22.7/576	3.5/90	375/170	32/2.2	-
100/80-17	A1689	52P	TL	2.50	23.3/592	4.0/101	441/200	40/2.8	-
80/100-18	A1689	47P	TL	1.85	24.3/617	3.1/80	386/175	32/2.2	✓



AE081



AE082

SIZE	PATTERN	LOAD/SPEED	TT / TL	RIM WIDTH (in.)	O.D. (inch/mm)	S.W. (inch/mm)	MAX LOAD (lbs/kgs)	INFLATE (psi/kgf/cm2)	E-MARK
110/70-17	AE081	54P	TL	3.00	23.1/586	4.3/110	467/212	32/2.2	✓
90/80-17	AE081	46P	TL	2.15	22.7/576	3.5/90	375/170	32/2.2	✓
100/80-17	AE081	52P	TL	2.50	23.3/592	4.0/101	441/200	40/2.8	✓
80/90-17	AE081	44P	TL	1.85	22.7/576	3.1/80	419/190	33/2.3	-
90/90-18	AE081	51P	TL	2.15	24.4/619	3.5/90	507/230	32/2.2	✓
120/80-16	AE082	60P	TL	2.75	23.5/598	4.7/119	551/250	32/2.2	✓
130/70-17	AE082	62P	TL	3.50	24.1/614	5.1/129	584/265	40/2.8	-



AE306



AE307

SIZE	PATTERN	LOAD/SPEED	TT / TL	RIM WIDTH (in.)	O.D. (inch/mm)	S.W. (inch/mm)	MAX LOAD (lbs/kgs)	INFLATE (psi/kgf/cm2)	E-MARK
90/90-18	AE306	51P	TL	2.15	24.4/619	3.5/90	507/230	32/2.2	✓
80/100-18	AE307	47P	TL	1.85	24.3/617	3.1/80	386/175	32/2.2	✓

Standard Street





A1084



AE707



AE737



AE757

SIZE	PATTERN	LOAD/SPEED	TT / TL	RIM WIDTH (in.)	O.D. (inch/mm)	S.W. (inch/mm)	MAX LOAD (lbs/kgs)	INFLATE (psi/kgf/cm2)	E-MARK
70/90-17	A1084	38P	TL	1.60	22.0/558	2.7/69	342/155	33/2.3	-
80/90-17	A1084	44P	TL	1.85	22.7/576	3.1/80	419/190	33/2.3	✓
2.75-17	AE707	41P	TL	1.85	23.1/588	3.0/75	386/175	32/2.2	✓
2.75-18	AE707	42P	TL	1.85	24.1/613	3.0/75	331/150	32/2.2	✓
2.25-17	AE737	4PR	TT	1.60	21.9/556	2.4/61	254/115	32/2.2	-
2.50-17	AE737	38L	TT / TL	1.60	22.0/568	2.6/65	291/132	32/2.2	✓
3.00-16	AE757	43P	TT / TL	1.85	22.5/571	3.0/76	364/165	32/2.2	-
2.75-17	AE757	41P	TT / TL	1.85	23.1/588	3.0/75	386/175	32/2.2	✓
3.00-17	AE757	50P	TT / TL	1.85	23.5/597	3.0/76	375/170	32/2.2	-
3.25-17	AE757	52P	TT / TL	2.15	23.9/607	3.2/81	452/205	32/2.2	-
2.50-18	AE757	40P	TT / TL	1.60	23.1/587	2.6/65	309/140	33/2.3	✓
2.75-18	AE757	42P	TT / TL	1.85	24.1/613	3.0/75	331/150	32/2.2	✓
3.00-18	AE757	47P	TT / TL	1.85	24.7/627	3.1/80	441/200	33/2.3	✓

Standard Street Front





A733A



A733B



A733C

SIZE	PATTERN	LOAD/SPEED	TT / TL	RIM WIDTH (in.)	O.D. (inch/mm)	S.W. (inch/mm)	MAX LOAD (lbs/kgs)	INFLATE (psi/kgf/cm2)	E-MARK
3.00-16	A733A	43P	TT / TL	1.85	22.5/571	3.0/76	364/165	32/2.2	-
2.25-17	A733A	33L	TT	1.60	21.9/556	2.4/61	254/115	32/2.2	-
3.00-17	A733A	50P	TT / TL	1.85	23.5/597	3.0/76	375/170	32/2.2	-
2.50-18	A733A	40P	TL	1.60	23.1/587	2.6/65	309/140	33/2.3	✓
2.50-17	A733B	38L	TT / TL	1.60	22.0/568	2.6/65	291/132	32/2.2	✓
2.75-18	A733C	48P	TT / TL	1.85	24.1/613	3.0/75	441/200	32/2.2	✓



APEXWAY PRODUCTS CORP.

Taiwan Head Office:

14F-5 No.238, Shizheng N. 2nd Rd., Xitun Dist., Taichung City 407, Taiwan, R.O.C.

Tel:+886-4-2251-2251 Fax:+886-4-2251-2129

E-mail:apex@apexway.com.tw

sportfire.apexway.com.tw