

Trailer Tire

www.apexway.com.tw



Ultra-Tac

SIZE	P.R.	PATTERN	RIM WIDTH(in)	O.D. (mm)	S.W. (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
ST175/80D13 B78-13ST	4	Ultra-Tac	5.00	610	178	35	241	500	1100
ST175/80D13 B78-13ST	6	Ultra-Tac	5.00	610	178	50	345	615	1360
ST175/80D13 B78-13ST	8	Ultra-Tac	5.00	610	178	65	448	710	1570
ST185/80D13 C78-13ST	4	Ultra-Tac	5.00	630	182	35	241	545	1200
ST185/80D13 C78-13ST	6	Ultra-Tac	5.00	630	182	50	345	670	1480
ST185/80D13 C78-13ST	8	Ultra-Tac	5.00	630	182	65	448	775	1710
ST205/75D14 F78-14ST	4	Ultra-Tac	5.50	665	205	35	241	650	1430
ST205/75D14 F78-14ST	6	Ultra-Tac	5.50	665	205	50	345	800	1760
ST205/75D14 F78-14ST	8	Ultra-Tac	5.50	665	205	65	448	925	2040

Trailer Tire

www.apexway.com.tw



Ultra-Tac

SIZE	P.R.	PATTERN	RIM WIDTH(in)	O.D. (mm)	S.W. (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
ST215/75D14 G78-14ST	6	Ultra-Tac	6.00	680	220	50	345	850	1870
ST215/75D14 G78-14ST	8	Ultra-Tac	6.00	680	220	65	448	975	2150
ST205/75D15 F78-15ST	6	Ultra-Tac	5.50	689	210	50	345	825	1820
ST205/75D15 F78-15ST	8	Ultra-Tac	5.50	689	210	65	448	975	2150
ST225/75D15 H78-15ST	6	Ultra-Tac	6.00	715	225	50	345	975	2150
ST225/75D15 H78-15ST	8	Ultra-Tac	6.00	715	225	65	448	1150	2540
ST225/75D15 H78-15ST	10	Ultra-Tac	6.00	715	225	80	551	1285	2830

Trailer Tire

www.apexway.com.tw



Ultra-Runner

SIZE	P.R.	PATTERN	RIM WIDTH(in)	O.D. (mm)	S.W. (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
4.80-8	4	Ultra-Runner	3.75	415	122	60	413	265	585
4.80-8	6	Ultra-Runner	3.75	415	122	90	620	345	760
5.70-8	4	Ultra-Runner	4.50	455	150	55	379	325	715
5.70-8	6	Ultra-Runner	4.50	455	150	80	551	412	910
5.70-8	8	Ultra-Runner	4.50	455	150	100	689	487	1070
4.80-12	4	Ultra-Runner	3.75	524	125	60	413	355	785
4.80-12	6	Ultra-Runner	3.75	524	125	90	620	450	990
5.30-12	4	Ultra-Runner	4.25	550	135	55	379	387	855
5.30-12	6	Ultra-Runner	4.25	550	135	80	551	475	1050
5.30-12	8	Ultra-Runner	4.25	550	135	100	689	570	1254

Trailer Tire

www.apexway.com.tw



Driver

SIZE	P.R.	PATTERN	RIM WIDTH(in)	O.D. (mm)	S.W. (mm)	INFLATE		MAX LOAD	
						(psi)	(kPa)	(kgs)	(lbs)
16.5x6.5-8 165/65-8	4	Driver	5.50	415	170	45	310	280	615
16.5x6.5-8 165/65-8	6	Driver	5.50	415	170	70	482	355	785
18.5x8.50-8 215/60-8	4	Driver	7.00	460	215	35	241	350	770
18.5x8.50-8 215/60-8	6	Driver	7.00	460	215	50	345	425	935
18.5x8.50-8 215/60-8	8	Driver	7.00	460	215	70	482	500	1100
20.5x8.0-10 205/65-10	4	Driver	6.00	520	200	35	241	410	905
20.5x8.0-10 205/65-10	6	Driver	6.00	520	200	50	345	500	1100
20.5x8.0-10 205/65-10	8	Driver	6.00	520	200	70	482	600	1320
20.5x8.0-10 205/65-10	10	Driver	6.00	520	200	90	620	690	1520